COMPACT AND SMART imageRUNNER ADVANCE 400i / 500i

Suitable for busy workgroups and departments, these compact imageRUNNER ADVANCE devices offer efficient mono output and intelligent document handling to optimise your workflows, save you money and secure your confidential information.



Productivity

- Unrivalled and consistent user experience through a large 17.8cm tiltable colour touch screen and intuitive menus
- Unique personalisation capabilities simplify and automate commonly performed tasks by user
- Colour duplex scanning and sending with native support for data formats such as searchable PDF and Open Office XML (Powerpoint) enables re-use and repurpose of digital content
- Integration with powerful document, capture and output management solutions provide process optimisation
- Up to 2,300 sheet paper capacity for busy workgroups and departments
- Time-saving automatic staple finishing option
- Support for mobile working.



Device and Information Security

- Award-wining and smart user authentication ensures control without impacting on user productivity or convenience
- Ability to disable functions by user to prevent unauthorised usage
- Secure Print and MailboxLite enhance document confidentiality
- A variety of standard features such as data erase, IP and MAC address filtering and IPSec protects the device and network data transfer
- An extensive range of options offer compliance to highest levels covering all aspects of information security
- Industry-first Data Loss Prevention and auditing of prints, copies, scans and faxes through uniFLOW.



Cost Control

- The functionality of many devices in one compact multifunctional device
- Efficient and reliable monochrome output for workgroups and departments
- User-based activity tracking provides visibility of print behaviour
- Apply policies and restrict usage at function level by user
- Efficient device monitoring, reporting and diagnostics for easy management and maintenance
- Ability to use shared resources, such as fax and Advance Space, from other iR-ADV devices
- Options for cost recovery and coin vending integration.



Integration

- Versatile imageRUNNER ADVANCE portfolio addresses the needs of all workplaces from small workgroups through to large departments and Corporate Reprographic Departments
- Native support for industry and network standards i.e. Genuine Adobe PostScript and PCL ensures hassle-free integration with ERP, CRM and other business information systems
- Consistent imageRUNNER ADVANCE platform and portfolio simplifies management and operation across a fleet
- Canon's powerful embedded MEAP & MEAP Web platform provides a strong link to a range of award-winning document, capture and output management solutions for process optimisation
- Easily configure, manage and upgrade your device, whether individually, or as part of a larger fleet using Canon's device management tools
- Shared resources across the network.



At a glance

- 40–50 ppm mono
- imageRUNNER
 ADVANCE platform
- Space saving, modular design
- 17.8cm colour tiltable touch screen
- Up to 2300 sheet capacity
- Up to A4 output
- Automatic staple finishing option



Sustainability

- Class leading Typical Electricity Consumption (TEC)* ratings
- Consumes as little as 1W in sleep mode
- Incorporates recycled materials and bio-plastics
- ENERGY STAR® qualified.





imageRUNNER ADVANCE 400i / 500i

imageRUNNER
ADVANCE

Printer Specifications Machine type	Monochrome A4 Laser Multifunctional (Reader/Printer standard)
Available Core functions	Print, Copy, Scan, Send and optional Fax
Print speed (BW)	IR-ADV 400i: Up to 40 ppm (A4 Single-sided), 25ppm (A5 Single-sided), 39ppm (A4 Double-sided), 22ppm (A5 Double-sided) IR-ADV 500i: Up to 50 ppm (A4 Single-sided), 25ppm (A5 Single-sided), 49ppm
	(A4 Double-sided), 22ppm (A5 Double-sided)
Printing method	Monochrome Laser Beam Printing
Print resolution Double sided printing	1200 dpi x 1200 dpi, 600 dpi x 600 dpi Automatic (Standard)
Printing from memory media	
	Direct printing available from USB memory key, Remote UI and Web Access* Supported file types: JPEG, TIFF, PDF, XPS** (* XPS print from websites is not supported) (** XPS requires DIRECT PRINT KIT (for PDF-XPS)-H1)
Printing from mobiles or	A range of software and MEAP-based solutions is available to provide printing from mobile
nternet-connected devices and cloud-based services	devices or internet-connected devices and cloud-based services depending on your requirements. Please contact your sales representative for further information.
Paper input (Standard)	1 x 550-sheet (80 gsm) cassette, 100-sheet (80 gsm) multi-purpose tray
Paper input (Option)	Up to 3 x 550-sheet cassettes (80 gsm) (Cassette Module-AA1)
Maximum paper input capacity	2300 sheets (80 gsm)
Paper output capacity	Without Finisher: 250 sheets (80 gsm) With Staple Finisher: 500 sheets without stapling (80gsm), 20 sets with stapling
Finishing capabilities	Standard: Group Optional Staple Finisher: Collate, Group, Staple Thin paper, Plain paper, Recycled paper, Colour paper, Heavy paper, Prepunched paper,
	Bond, Transparency, Label, Letterhead, Bond paper, Envelope
Supported media types	Cassette/s: Plain paper, Recycled paper, Colour paper, Heavy paper, Pre-punched paper, Envelope* "Envelope support via drawer 2 only. Requires optional Envelope Cassette-E1 Multi-purpose tray: Plain paper, Recycled paper, Colour paper, Heavy paper, Pre-punched
Supported modia sizes	paper, Bond, Transparency, Label, Envelope (No.10 (COM10), Monarch, ISO-C5, DL) Paper Drawer 1, 3 and 4: Standard size: A4, A5, B5, Legal, Letter, Executive, Statement
Supported media sizes	Paper Drawer 1, 3 and 4: Standard size: A44, A5, B5, Legal, Letter, Executive, Statement Paper Drawer 2: Standard size: A4, A5, B5, Legal, Letter, Executive, Statement, Envelopes* (No.10 (COM10), Monarch, ISO-C5, D1) 'Requires optional Envelope Cassette-E1 Multi-purpose tray: Standard size: A4, A5, B5, Legal, Letter, Executive, Statement, Custom size (99 mm to 216 mm × 140 mm to 356 mm), Envelopes (No.10 (COM10), Monarch, ISO-C5,D1)
Supported media weights	Cassette/s: 64 to 105 g/m², Multi-purpose tray: 64 to 128 g/m², Duplex: 64 to 105 g/m²
Page Description Language(s)	UFRII , PCL5e/6, Adobe PostScript Level 3 (Standard on all models)
Fonts	PCL fonts: 93 Roman, 10 Bitmap, 2 OCR fonts, Andale 4, PS fonts: 136 Roman fonts
Operating System compatibility	UFRII: Windows XP/Server 2003/Vista/Server 2008/Windows 7/Server 2008R2/ Windows 8/Server 2012, MAC OS X (10.5.8 or later)
	PCL: Windows XP/Server 2003/Vista/Server 2008/Windows 7/Server 2008 R2/ Windows 8/Server 2012
	PS: Windows XP/Server 2003/Vista/Server 2008/Windows 7/Server 2008 R2/
	Windows 8/Server 2012, MAC OS X (10.5.8 or later) PPD: MAC OS 9.1 or later, MAC OS X (10.3.9 or later), Windows 2000/Windows XP/Windows
	Vista/Windows 7/Windows 8
	Please refer to http://software.canon-europe.com/ for availability of print solutions for other operating systems and environments including AS/400, UNIX, Linux and
	Citrix. Some of these solutions are chargeable.
Copy Specifications	SAP Device Types are available via the SAP Market Place.
Copy speed	iR-ADV 500i: Up to 50 ppm (A4), iR-ADV 400i: Up to 40 ppm (A4)
First Copy Output Time (FCOT)	Approx. 5.0 seconds or less
Copy resolution	Reading: 600 dpi x 600 dpi Printing: 1200 dpi x 1200 dpi for characters/lines, 600 dpi x 600 dpi for graphics/images
Multiple copy	Up to 999 copies
Reduction/Enlargement	Zoom: 25-400 % in 1% increments
Scan Specifications	Fixed Zoom Ratio: 25 %, 50 %, 70 %, 100 %, 141 %, 200 %, 400 %
Optional/Standard	Standard on all models
Supported media size/s	A4, A5, B5, Custom sizes (W x L): Min. 140 mm x 140 mm, Max. 356 mm x 216 mm
Supported media weight/s	Single-sided scanning: 42 to 128 gsm/64 to 128 gsm (Mono/Colour), Double-sided scanning: 50 to 128 gsm/64 to 128 gsm (Mono/Colour)
Scan resolution	Mono Scan: 100 dpi, 150 dpi, 200 dpi x 100 dpi, 200 dpi, 300 dpi, 200 dpi x 400 dpi,
	400 dpi, 600 dpi Colour Scan: 100 dpi, 150 dpi, 200 dpi x 100 dpi, 200 dpi, 300 dpi
Double sided scanning	2-sided to 2-sided (Automatic)
Scan speed (A4, 300 dpi)	Mono single-sided: 50 ipm/A4(600dpi/300dpi) Mono double-sided: 32 ipm/A4(600dpi/300dpi) Colour single-sided: 50 ipm/A4(300dpi)
	Colour double-sided: 32 ipm/A4(300dpi)
Scan methods	Push Scan: Colour Universal Send functionality is standard. Integration with a range of optional MEAP-based capture software adds powerful worflow and conversion
	capabilties. Please contact your sales representative for further information.
	Pull Scan: TWAIN/WIA Pull scanning available on all models. Scan to USB Memory Key Scan to Mobiles, internet-connected devices and cloud-based services: A range of
	solutions is available to provide scanning to mobile devices, internetconnected devices and cloud-based services depending on your requirements. Please contact your sales
	representative for further information.
Pull scan specifications	TWAIN via Network TWAIN Driver (Colour Network ScanGear) Supported OS: Windows 2000/Windows XPWIndows Server 2003/Windows Ststa/Windows Server 2008/ Windows 7/Windows 8 (32 bit, 64 bit in compatibility mode)* WIA via Network WIA Driver Supported OS: Windows Vista/Windows Server 2008/Windows 3/Windows 1/20 bit 64 bit 100 bit
	7/Windows 8 (32 bit, 64 bit)* *The drivers are available via http://software.canon-europe.com/
Send Specifications	
Optional/Standard Send resolution	Standard on all models 100 dpi, 150 dpi, 200 dpi x 100 dpi, 200 dpi, 300 dpi, 200 dpi x 400 dpi, 400 dpi, 600 dpi
Destinations	E-Mail/Internet FAX (SMTP), Fax(option), PC (SMB, FTP, WebDAV), Google
Address Deal-/C	Drive with Cloud Connect for iR-ADV MEAP application
Address Book/Speed dials File formats	LDAP(Max. 2000 searchable), Local (Max. 1800 including 200 Speed dials) TIFF, JPEG, PDF, XPS, PDF/XPS (compact), PDF/A-1b, Searchable PDF/XPS,
	Office Open XML (PowerPoint)
Optional Universal Send Feature Sets	UNIVERSAL SEND ADVANCED FEATURE SET-Et: Create outline PDF (Trace and Smooth) and Adobe Reader Extensions PDF. UNIVERSAL SEND SECURITY FEATURE SET-DI: Send encrypted PDF and add digital device signature to PDF/XPS files. UNIVERSAL SEND DIGITAL ILSES SIGNATURE IN PERIORS.
Fax Specifications	SEND DIGITAL USER SIGNATURE KIT-C1: Add digital user signature to PDF/XPS files.
Optional/Standard	Optional on all models (requires SUPER G3 FAX BOARD-AM1)
Modem speed	Super G3 33.6kbps (Up to 3 seconds per page (see [1]))
ax resolution	Standard: 200 x 100 dpi, Fine: 200 x 200 dpi, Super fine: 200 x 400 dpi, Ultra fine: 400 x 400 dpi
-AX memory	Up to 6000 pages (see [1])
Speed dials	Max. 200
Group dials/destinations	Max. 199 dials
Sequential broadcast Memory backup	Max. 256 addresses Yes (Approx. 3 hours)
Other features	Fax Forwarding, Dual Access, PC Fax (TX only)

canon.co.nz/business 0800 222 666

2377-v1-09/13

General Specifications	
Warm-up Time	Approx. 34 seconds from power ON (Normal mode), 10 seconds from power ON (Quick Start mode)
Recovery from sleep mode	Start mode) 10 seconds or less
Interface type	USB 2.0 Hi-Speed,1000BaseT/100Base-TX/10Base-T, 1 x USB Host (Front), 2 x USB Host(Rear)
Network protocols	TCP/IP* (LPD/Port 9100/WSD/IPP/IPPS/SMB/FTP), IPX/SPX (NDS, Bindery), AppleTalk *IPv4/IPv6 support Recommended third party wireless solution is Silex SX-2500CG. For more details please refer to www.silex-europe.com
Processor Speed	1.66 Ghz
Memory	1.5 GB
Hard Disk Drive	160 GB Hard Disk Drive (Usable space 80 GB)
Control panel	17.8 cm (7 inch) WVGA Colour TFT LCD Touch & Tiltable Panel
Dimensions (W x D x H)	560 mm x 567 mm x 633 mm (standard), 560 mm x 567 mm x 752 mm (with 1 optional cassette), 560 mm x 567 mm x 868 mm (with 2 optional cassettes), 560 mm x 567 mm x 984 mm (with 3 optional cassettes)
Installation space (W x D)	787 mm x 567 mm (Main unit + Multi-purpose tray open + Cassette drawers closed) 1182 mm
	x 567 mm (Main unit + Staple Finisher + Multi-purpose tray open + Cassette drawers closed)
Weight	47.9kg excluding Toner
Operating environment Power Source	Temperature: 10 to 30°C (50 to 86°F), Humidity: 20 to 80 % RH (no condensation) 220-240 V (±10 %), 50/60 Hz (±2 Hz), 4.3-5.6 Amp
Power Consumption	Maximum: Approx. 1.6 KW
	Standby: Approx. 53.72 W
	Sleep mode: Approx. 1W or less (see [2]) Typical Electricity Consumption (TEC) rating (see [3]): 2.4 kWh (iRADV 500i) / 1.873 kWh (iR-ADV 400i)
Noise Levels	Sound Pressure (see [4])
	Active: 75 dB or less (iR-ADV 500i), 73 dB or less (iR-ADV 400i)
Coffessor and printer management	Standby: 53 dB or less
Software and printer management	MEAP (Multifunctional Embedded Application Platform): A powerful JAVA-Embedded Platform for Canon devices which integrates the device with a wide range of Canon and
	third party software solutions.
	Universal Login Manager: iR-ADV software for smaller businesses offering convenient login, personalisation as well as user-based usage tracking and control by function.
	mobile PRINT & SCAN: Simple serverless iR ADV software enabling printing from and
	scanning to Android and iOS mobiles and tablets.
	MEAP Web: Web service alternative to MEAP that allows MFP applications to be developed
	and deployed via web services IW Management Console: Server-based software for centralised management of a fleet
	of devices
	eMaintenance: embedded RDS allows remote eMaintenance services such as meter
	capture, automatic consumables management and remote diagnostics. Content Delivery System: Allows the remote distribution of firmware, iR options and
	MEAP applications
	Remote User Interface (RUI): Web-based interface to each device that helps to provide
	remote device management and control. Colour Network ScanGear: TWAIN-compliant scanner driver that enables computers on a
	network to use the pull scan functionality of the device.
	Canon Driver Configuration Tool: A utility for changing the factory default settings of Canon
	print drivers (Available via service only) IW-DESKTOP: Drag-and-Drop print publishing software to easily combine documents and
	apply finishing to create professional-looking documents
	REMOTE OPERATORS SOFTWARE: Allows use of device control panel screens from
	remote computers. For details of other software including MEAP software, please contact your sales
	representative
Security Features	Standard: IP/Mac Address Filtering, IPSEC, SNMP V3.0, IEEE 802.1X, Trusted Platform Module (TPM), Secure Print, HDD Password Lock, Data Erase, Universal Login Manager, Department ID, SSO-H, Access Management System.
	Optional: Encrypted Secure Print, Encrypted PDF, HDD Encryption, User and Device signatures, Secure Watermarks, MailboxLite.
	The following items require uniFLOW: My Print Anywhere secure print, Data Loss Prevention.
Consumables Toner bottle	C-EXV 43 Black Toner (Yield: 15200 pages (see [5]))
Other options	C-EAV 43 Black Tottlet (Tield: 13200 pages (See [3]))
Staple Finisher1	Staple Finisher-R1. Number of Trays: 1. Stack Capacity: With stapling: 20 sets. Without
Supermisier	staplier Imislet Mr. Nufficer on Jays. 1. Stack opberty. Win Sasping, 220 sets. Windows stapling: 500 sheets. Maximum Stapling capacity: Up to 50 sheets. Paper Weight. 64 to 128 g/m². Staple Position: Single (Top-Left). Dimensions (W x D x H): 798 mm × 395 mm × 263 mm Weight. Approx. 10.5 kg.
Finisher N/A	Staple Finisher 2, Booklet Finisher
Cassette module	Cassette Module-AA1 Description: Optional cassette module with 550 sheets paper
Hanking a second of	capacity. Up to 3 cassette units can be added to a main unit. Dimensions (W x D x H): 540 mm x 500 mm x 119 mm. Weight: Approx. 7.7 kg
Hardware accessories 1	Plain Pedestal Type-B1: The pedestal can be placed under the standard/optional cassette module to raise the device when free-standing. This is a higher pedestal suitable for use
	with the standard cassette or one additional cassette module. (Height of Pedestal: 300 mm) Plain Pedestal Type-C1: The pedestal can be placed under the standard/optional cassette module to raise the device when free standing. This is a lower pedestal suitable for use
	with an additional two or three cassette modules. (Height of Pedestal: 94 mm)
	Envelope Cassette -E1: Attaches to cassette "2" for easy envelope feeding.
Hardware accessories 2	MICARD PLUS PROXIMITY CARD READER: A proximity card reader for card-based user authentication, supporting multiple card technologies (HID, HITag, Casi Rusco, Indala and
	MiFare etc.):
Print controller accessories	BARCODE PRINTING KIT-D1: Enables barcode printing via jet caps technology.
Document-publishing	iW DESKTOP: Drag-and-Drop print publishing software which easily combines documents
	from different sources, applies finishing to create professional looking documents and seamlessly links to the printer. Includes PDF creation, annotation and compression capabilities for digital workflows-such as proofing and authorization.
System accessories	WEB ACCESS SOFTWARE-J1: Provide access to websites and MEAP Web applications.
.,	SUPER G3 FAX BOARD-AM1: Adds fax functionality:
	Super G3 2ND LINE FAX BOARD-AM1: Adds second fax line. REMOTE FAX KIT-A1: Enables the device to send and receive fax from another compatible
	device connected with a fax board.
	IC CARD READER BOX-A1: A Box to hold and secure an IC Card Reader such as MiCard
	Reader to the device.
	COPY CONTROL INTERFACE KIT-A1: Allows connection (CCVI-I/F) between 3rd party copy control terminal and Canon's iR ADV range for cost recovery use:
Device security accessories	HDD DATA ENCRYPTION KIT-C6: Encrypts all image data and device settings before storing
	them on the hard drive of the device.
Document security accessories	SECURE WATERMARK-B1: Deters duplication of sensitive documents by embedding hidden
	watermarks that become visible when copied. ENCRYPTED PRINTING SOFTWARE-D1: Encrypts the print job in transit to the device and
	requires a password at the printer before sensitive documents can be printed.
Accessibility accessories	ADF ACCESS HANDLE-A1: Attaches to the document feeder, making access easier for
	seated users. REMOTE OPERATORS SOFTWARE KIT-B1: Allows use of device control panel screen from
	remote computers.
Other options	STAPLE-P1: Plain staples for Staple Finisher R1
(1) Beand on ITH T Standard Chr.	Contifferable on a real anguage title life.

Uner options

SIAPLE-YE, Main staples for Stople - Inistinct H

[1] Based on TILT Standard Chart Not

[2] I want sleep mode may not be possible in all circumstances. Certain network

configurations and options may prevent the device from entering deep sleep

mode. Please refer to the user guide for more information.

[3] Typical Electricity Consumption (TEC) rating represents the typical electricity

consumed by a product during I week, measured in kilowatt-house (kWh). The

tests methodology is defined by Energy Star (http://www.eu-energystar.org).

[4] Declared notice emission in accordance with ISO 7779

[5] Based on 80; coverage (AV)

[6] Based on 80; coverage (AV)

Adobe PotSnigt 3

Adobe PotSnigt 3





















