

BIG COLOUR PERFORMANCE MEETS SMALL SIZE

C250i / C350i

Canon imageRUNNER ADVANCE



Compact and powerful, these new additions perform as an integral part of your fleet or as a stand alone colour device.

The C250i and C350i A4 Colour devices come fully loaded with the latest system features and can be installed in both desktop and floor standing environments. These clever, versatile devices are ideal for large enterprises who want an affordable, network-integrated device to reliably output professional quality, as well as being ideal for small business who want more capabilities and greater productivity.

Productivity / Performance

Create high quality documents with superior colour, superb print quality and staple finishing. Save time with advanced scanning into business applications, embedded OCR and centralised configuration management.



Integration

Seamlessly integrate with back end systems with Canon's powerful embedded MEAP.



Sustainability

Reduce your impact. C250i and C350i incorporate recycled material and bio-plastics, Energy Star qualified, front runner TEC rating. Lower your energy consumption with less than 1W sleep mode.



Cost Control

Integrated authentication software, auto duplex and B/W controls help to manage your output.



Security

Advanced security features such as password protection, data erase, encryption and scan lock to safeguard your data.



At a glance

- 25–35ppm B/W and Colour
- Scan, fax, copy & print in colour or B/W
- 7" (17.8cm) colour tiltable touch screen



- Up to 2,300 sheet capacity
- Staple finishing capabilities
- MEAP applications to enhance workflows and increase productivity
- Modular design

Canon

*achieve more.
beyond technology.*

imageRUNNER ADVANCE C250i / C350i



Basic Specifications

Operation Panel	7" Colour WVGA LCD display
Memory	Standard 2GB Hard Disk Drive 80GB
Network Interface Connection	Ethernet 10Base-T/100Base-TX/1000BaseT
Other Interface (Standard)	USB 2.0 (Host) x 3, USB 2.0 (Device) x 1
Copy/Print Speed	C250i: Up to 25 ppm (A4) C350i: Up to 35 ppm (A4)
First-Copy-Out Time	C250i: 8.4 sec BW / 10.5 sec colour C350i: 5.9 sec BW / 7.4 sec colour
Paper Sources (80gsm)	Standard: 550 sheets (desktop device) Optional: 3 x 550-sheet Cassette Feeders (Cassette Pedestal) Maximum: 2,300 sheets
Output Paper Capacity	Without finisher: 250 sheets With Staple finisher: 500 sheets without stapling, 20 sets with stapling
Finishing Capabilities	Standard: Group, Collate Optional Staple Finisher: Group, Collate, Staple
Warm-up Time	From Power On: 34 seconds From Sleep Mode: 10 seconds Quick Startup Mode: 10 seconds
Power Requirements	220-240V AC, 50/60 Hz, 4.0 AMPS
Power Consumption	Maximum: 1.5kW Sleep Mode: 1W or less ¹ Energy Star Qualified: Yes
Dimensions (W x D x H)	Main Unit: 511mm x 621mm x 610mm Main Unit + Cassette Pedestal: 511 x 621 x 1035 mm
Installation Space (W x D)	Main Unit: 903 mm x 621 mm Main Unit + Staple finisher: 903 mm x 1008 mm
Weight	Approximately 44kg
Toner (Estimated Yield at 5% Coverage)	TG65: 19,000 (Black) / 21,500 (Colour)

Print Specifications (Standard)

Printing Resolution	600 x 600 dpi
PDL Support	Standard: UFR II, PCL 5/6, Genuine Adobe PostScript 3, Canon PPDs
Acceptable Paper Type	Cassette/s: Thin paper, Plain paper, Recycled paper, Colour paper, Heavy paper, Pre-punched paper, Envelopes ² Bypass: Thin paper, Plain paper, Recycled paper, Colour paper, Heavy paper, Pre-punched paper, Transparency, Labels, Envelopes (No.10 (COM10), Monarch, ISO-C5, DL)
Acceptable Paper Sizes	Cassette 1: A4, A5, B5, Legal, Letter, Executive, Statement, Envelopes (No. 10 (COM10), Monarch, DL) Custom size (98.4 to 216 mm x 190.5 to 355.6 mm) Cassette 2/3/4: A4, A5, B5, Legal, Letter, Executive, Statement Custom size (98.4 to 216 mm x 190.5 to 355.6 mm) Bypass: A4, B5, A5, Legal, Letter, Executive, Statement, Envelope (No. 10 (COM10), Monarch, ISO-C4, DL) Custom size (98.4 to 216 mm x 148 to 355.6 mm)
Acceptable Paper Weights	Cassette/s: 60 to 163gsm Bypass: 60 to 220gsm Duplex: 60 to 163gsm
Print Driver Supported OS	PCL: Windows XP/Server 2003/Vista/Server 2008/Windows 7/Server 2008 R2/Windows 8/Windows 8.1/Server 2012/Server 2012 R2 PS: Windows XP/Server 2003/Vista/Server 2008/Windows 7/Server 2008 R2/Windows 8/Windows 8.1/Server 2012/Server 2012 R2, MAC OS X (10.5.8 or later) UFR II: Windows XP/Server 2003/Vista/Server 2008/Windows 7/Server 2008 R2/Windows 8/Windows 8.1/Server 2012/Server 2012 R2, MAC OS X (10.5.8 or later) PPD: MAC OS 9.1 or later, MAC OS X (10.3.9 or later), Windows XP/Windows Vista/Windows 7/Windows 8
Direct Print	Supported Media: USB memory key, Remote UI and Web Access ³ Supported file types: JPEG, TIFF, PDF, XPS ⁴

* All specifications subject to change without notice

¹ 1 watt sleep mode may not be possible in all circumstances. Certain network configurations and options may prevent the device from entering deep sleep

² Envelope support via standard cassette 1 only

³ XPS print from websites is not supported

⁴ XPS requires DIRECT PRINT KIT (for PDF/XPS)-H1

⁵ Based on ITU-T Standard Chart No. 1 mode. Please refer to the user guide for more information

All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Certifications and compatibility



Scan Specifications

Scan Type	Duplexing Automatic Document Feeder
Acceptable Originals	Paper Size: A4, A5, B5, Custom sizes: 140 mm to 216 mm x 128 mm to 356mm (when fed through the DADF) Paper Weight: Single-sided scanning: 50 to 105 gsm (DADF) Double-sided scanning: 64 to 105 gsm (DADF)
Scan Resolution (dpi)	BW: Up to 600 x 600 dpi Colour: Up to 300 x 300 dpi
Scanning Speed (A4, 300 dpi)	C250i: B&W: single-sided 25ipm, double-sided 9 ipm Colour: single-sided 25ipm, double-sided 9 ipm C350i: B&W: single-sided 35ipm, double-sided 11ipm Colour: single-sided 35ipm, double-sided 11ipm
Scan Methods	Push Scan: Colour Universal Send functionality is standard. Integration with a range of optional MEAP based capture software adds powerful workflow and conversion capabilities. Please contact your sales representative for further information. Pull Scan: TWAIN/WIA Pull scanning available on all models. Scan to USB Memory Key: Available on all models Scan to mobiles, internet-connected devices and cloud-based services: A range of solutions is available to provide scanning to mobile devices, internet-connected devices and cloud-based services depending on your requirements. Please contact your sales representative for further information.
Paper Capacity (80gsm, A4)	50 sheets

Colour Send Specifications

Send Resolution	Up to 600 x 600 dpi
Destinations	E-Mail/Internet FAX (SMTP), Fax (option for C250i/C350i), PC (SMB, FTP, WebDAV), Google Drive with Cloud Connect for iR-ADV MEAP application
Address Book/Speed Dials	LDAP (Max. 2000 searchable), Local (Max. 1800 including 200 Speed dials)
File Formats	TIFF, JPEG, PDF, XPS, PDF/XPS (compact), PDF/A-1b, Searchable PDF/XPS, Office Open XML (PowerPoint)
Optional Universal Send Feature Sets	Advanced Feature Set-D1: Create outline PDF (Trace and Smooth) and Adobe Reader Extensions PDF Security Feature Set-D1: Send encrypted PDF and add digital device signature to PDF/XPS files. Digital User Signature Kit-C1: Add digital user signature to PDF/XPS files.

Security Specifications

Standard	IP/Mac Address Filtering, IPsec, SNMP V3.0, IEEE 802.1X, Trusted Platform Module (TPM), Secure Print, Hard Disk Drive Password Lock, Data Erase, Universal Login Manager, Department ID, SSO-H, MailboxLite, Access Management System, Adobe Right Management compatibility
Optional	Encrypted Secure Print, Encrypted PDF, HDD Encryption, User and Device signatures, Secure Watermarks, MailboxLite. The following items require uniFLOW: My Print Anywhere secure print, Data Loss Prevention.

Fax Specifications (Optional)

Requires	Canon Super G3 FAX Board-AN1
Number of Connection Lines	1
Modem Speed	Super G3: 33.6 Kbps
Fax Resolution	Standard: 200 x 100 dpi Fine: 200 x 200 dpi Super fine: 200 x 400 dpi Ultra fine: 400 x 400 dpi
Fax Memory	Approximately 6,000 pages ⁵
Speed Dials (one touch)	Max. 200
Group Dials/Destinations	Max. 199 dials
Sequential Broadcast	Max. 256 destinations in a group address
Memory Backup	Yes
Other Features	Fax Forwarding, Dual Access, PC Fax (TX only)

External Staple Finisher (Optional)

Number of Trays	1
Loading Capacity	500 sheets non-stapled, 20 sheets stapled
Paper Weight	60 to 220gsm
Staple Position	Top-Left Corner
Stapling Capacity	Up to 30 sheets
Dimensions (W x D x H)	589 x 459 x 301 mm
Weight	Approximately 14kg

Cassette Pedestal (Optional)

Dimensions (W x D x H)	511 x 508 x 425 mm
Weight	Approximately 19kg

Other Optional Accessories

Canon PCL International Font Set-B1, Canon Direct Print Kit (for PDF)-H1, Canon Direct Print Kit (for XPS)-H1, Canon Barcode Printing Kit-D1, Canon Universal Send Advanced Feature Set-D1, Canon Universal Send Security Feature Set-D1, Canon Universal Send Digital User Signature Kit-C1, Canon Secure Watermark-B1, Canon Document Scan Lock Kit-B1, Canon Remote Fax Kit-A1, Canon ADF Access Handle-A1, Canon HDD Data Encryption Kit-C6, Canon Encrypted Printing Software-D1, Access Management Kit-B1, Canon Web Access Software-H1, Canon IC Card Reader Box-A1, Canon Serial Interface Kit-K2, Canon Copy Control Interface Kit-A1, Canon Cassette Heater Unit-39

canon.com.au/business

Follow us on Twitter @CanonBusinessAU

1800 444 199

2910-v1-8/14

achieve more.
beyond technology.